

EUROLUB KERAMIKPASTE

Performance:	Keramikpaste is a universal paste with excellent lubricating properties. The product protects (screw) connections and keeps them well, even after prolonged exposure to heat and atmospheric influences. The product has water-displacing properties and protects against corrosion. The liability is excellent. In the formulation of the product, no metals such as copper, nickel, molybdenum, etc. were used, but was based on natural resources. The Keramikpaste is therefore almost not harmful to the environment.
---------------------	--

Application:	Keramikpaste is to be used as assembly paste for all assembly applications such as individual parts and screw connections that are usually mounted or lubricated with metal pastes. Can also be used as thin-film lubrication where low sliding speeds, very high pressure loads, high wear, stickslip, oscillating movements, vibrations and tribocorrosion occur. Not to be used as bearing grease!
---------------------	---

Directions:	Apply thinly on a, if possible, clean surface. Do not mix with normal fats.
--------------------	---

Delivery:	Art.-Nr. 003818	12 x 200 ml
------------------	-----------------	-------------

Technical Data:			
Data	Unit	Test method	EUROLUB Keramikpaste
Density, 20°C	g/cm ³		1,26
Flash point	°C		275
VOC (EU)	g/l		0

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 24.08.2020, made: 08.10.2018
	Referenz: tl0084416
	name: 003818_TDS_EN
	Seite 1 von 1