

EUROLUB ECO B12 0W-30

Description/Applications:

This modern fuel economy motor oil is produced with special base oils and a well-balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at high temperatures
- a very good detergency and dispersion power

Can be used with:

ACEA C2
BMW Longlife-12FE

Delivery:

Art.-Nr. 208020	20 Liter	can
Art.-Nr. 208060	60 Liter	hobbock
Art.-Nr. 208208	208 Liter	drum
Art.-Nr. 208100	1000 Liter	IBC

Technical Data:

Data	Unit	Method	EUROLUB ECO B12 0W-30
Density at 15°C	kg/L	ASTM D 4052	0,841
Viscosity at 40°C	cSt	ASTM D 445	53,4
Viscosity at 100°C	cSt	ASTM D 445	9,9
Viscosityindex (VI)		ASTM D 2270	175
Flash point (COC)	°C	ASTM D 92	234
Pourpoint	°C	ASTM D 6892	-39

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.