

## EUROLUB ECO LL 0W-30

<b>Description / Applications:</b>	<p>A fuel economy, universal motor oil, developed according the most recent technology, based on specially selected base oils and a well balanced choice of advanced additives to obtain the following properties:</p> <ul style="list-style-type: none"> <li>- a lower fuel consumption</li> <li>- mid SAPS content</li> <li>- suitable for modern catalysts</li> </ul> <p>This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.</p>
------------------------------------	---

<b>Can be used with:</b>	<p>ACEA C3 VW 504.00 / 507.00 Porsche C30</p>
--------------------------	---

<b>Delivery:</b>	<table> <tr> <td>Art.-Nr. 212001</td> <td>12 x 1 Liter</td> <td>bottle</td> </tr> <tr> <td>Art.-Nr. 212005</td> <td>4 x 5 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 212020</td> <td>20 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 212060</td> <td>60 Liter</td> <td>hobbock</td> </tr> <tr> <td>Art.-Nr. 212208</td> <td>208 Liter</td> <td>drum</td> </tr> <tr> <td>Art.-Nr. 212100</td> <td>Container</td> <td>IBC</td> </tr> </table>	Art.-Nr. 212001	12 x 1 Liter	bottle	Art.-Nr. 212005	4 x 5 Liter	can	Art.-Nr. 212020	20 Liter	can	Art.-Nr. 212060	60 Liter	hobbock	Art.-Nr. 212208	208 Liter	drum	Art.-Nr. 212100	Container	IBC
Art.-Nr. 212001	12 x 1 Liter	bottle																	
Art.-Nr. 212005	4 x 5 Liter	can																	
Art.-Nr. 212020	20 Liter	can																	
Art.-Nr. 212060	60 Liter	hobbock																	
Art.-Nr. 212208	208 Liter	drum																	
Art.-Nr. 212100	Container	IBC																	

### Technical Data:

Data	Unit	Method	EUROLUB EVO LL 0W-30
Density at 15°C	kg/L	D 4052	0,842
Viscosity at 40°C	cSt	D 445	64,0
Viscosity at 100°C	cSt	D 445	12,0
Viscosityindex (VI)		D 2270	178
Flash point (COC)	°C	D 92	195
Pourpoint	°C	D 6892	-51

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	print: 24.08.2020, made 31.01.2018
	Referenz: NSA0644, 29.11.2017
	Name: 212xxx_TDS_EN
	Seite 1 von 1