

EUROLUB Multitec 5W-30

Description / Applications:	This fuel economy motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below. This oil is fully backwards compatible with Ford M2C 913-A, B and C.
------------------------------------	---

Can be used with:	ACEA A5/B5 API SL/CF Ford WSS-M2C913-D (covers 913-A/-B/-C) Renault RN0700 Jaguar Land Rover STJLR.03.5003
--------------------------	--

Delivery:	Art.-Nr. 214001	12 x 1 Liter	bottle
	Art.-Nr. 214004	4 x 4 Liter	can
	Art.-Nr. 214005	4 x 5 Liter	can
	Art.-Nr. 214020	20 Liter	can
	Art.-Nr. 214060	60 Liter	hobbock
	Art.-Nr. 214208	208 Liter	drum
	Art.-Nr. 214100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB MULTITEC 5W-30
Density at 15°C	kg/L	D 4052	0,849
Viscosity at 40°C	cSt	D 445	59
Viscosity at 100°C	cSt	D 445	10,2
Viscosityindex (VI)		D 2270	163
Flash point (COC)	°C	D 92	234
Pourpoint	°C	D 6892	-33

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.