

EUROLUB ECO PS-C 0W-30

Description / Applications:

This universal, fuel economy, "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters.

Can be used with:

ACEA C2
PSA B71 2312
Fiat 9.55535-DS1/GS1
Iveco 18-1811 SC1 LV

Delivery:

Art.-Nr. 219001	12 x 1 Liter	bottle
Art.-Nr. 215005	4 x 5 Liter	can
Art.-Nr. 219020	20 Liter	can
Art.-Nr. 219060	60 Liter	hobbock
Art.-Nr. 219208	208 Liter	drum
Art.-Nr. 219100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB ECO PS-C 0W-30
Density at 15°C	kg/L	D 4052	0,844
Viscosity at 40°C	cSt	D 445	55,0
Viscosity at 100°C	cSt	D 445	10,1
Viscosityindex (VI)		D 2270	170
Flash point (COC)	°C	D 92	230
Pourpoint	°C	D 6892	-42

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.