

EUROLUB SUPER ECO 0W-16

Description/Applications:	SUPER ECO 0W-16 is a fuel economy, specially composed SAE 0W-16 motor oil. It is recommended for use in petrol engines in passenger cars of Japanese OEM's, equipped with the latest techniques.
----------------------------------	--

Can be used with:	API SN
--------------------------	--------

Delivery:	Art.-Nr. 220001	12 x 1 Liter	bottle
	Art.-Nr. 220005	4 x 5 Liter	can
	Art.-Nr. 220020	20 Liter	can
	Art.-Nr. 220060	60 Liter	hobbock
	Art.-Nr. 220208	208 Liter	drum
	Art.-Nr. 220100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB SUPER ECO 0W-16
Density at 15°C	kg/L	D 4052	0,846
Viscosity at 40°C	cSt	D 445	36,4
Viscosity at 100°C	cSt	D 445	7,2
Viscosityindex (VI)		D 2270	167
Flash point (COC)	°C	D 92	216
Pourpoint	°C	D 6892	-39

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 24.08.2020, made 07.05.2018
	Referenz: NSA06.88, 26.04.2018
	Name: 222xxx_TDS_EN
	Seite 1 von 1