PRODUCT INFORMATION



EUROLUB CLEANSTAR C2 5W-30

Description/Applications:	This universal, fuel economy, low SAPS motor oil is recommended			
	for use in petrol and diesel engines, with or without turbo-charging,			
	in passenger cars and delivery vans with extended oil drain intervals.			
	Due to its low SAPS content this product can be applied in vehicles			
	with modern three way catalysts and diesel particle filters.			

Can be used with:	ACEA C2		
	API SN/CF		
	PSA B71 2290		
	Renault RN 0700		
	Fiat 9.55535-S1		

Delivery:	ArtNr. 223001	12 x 1 Liter	bottle
	ArtNr. 223005	4 x 5 Liter	can
	ArtNr. 223020	20 Liter	can
	ArtNr. 223060	60 Liter	hobbock
	ArtNr. 223208	208 Liter	drum
	ArtNr. 223100	Container	IBC

Technical Data:					
Data	Unit	Method	EUROLUB CLEANSTAR C2 5W-30		
Density at 15°C	kg/L	D 4052	0,853		
Viscosity at 40°C	cSt	D 445	58,0		
Viscosity at 100°C	cSt	D 445	10,2		
Viscosityindex (VI)		D 2270	162		
Flash point (COC)	°C	D 92	235		
Pourpoint	°C	D 6892	-33		

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.