

## EUROLUB LOWCARGO 5W-30

<b>Description / Applications:</b>	This lubricant has mainly been developed for heavy diesel engines even under the toughest operation conditions and all over the year round. This product is very suitable for Euro 5 and Euro 6 engines in combination with diesel fuel with a low Sulphur content. This engine oil is also suitable for application in engines with or without particle filters and exhaust catalysts. This motoroil is one of the group "low SAPS" lubricants.
------------------------------------	--

<b>Can be used with:</b>	ACEA E6 / E7 / E9 API CK-4 / SN JASO DH-2 MB 228.51 Volvo VDS-4.5 Renault VI RLD-3 Mack EOS-4.5 Deutz IV-18 LA MTU MTL 5044 Typ 3.1 MAN M 3775 / 3677 / 3477 Caterpillar ECF-3 Cummins CES 20086 Detroit Diesel DDC 93K222 Scania
--------------------------	--

<b>Delivery:</b>	Art.-Nr. 232005      4 x 5 Liter      can Art.-Nr. 232020      20 liter          plastic can Art.-Nr. 232060      60 liter          hobbock Art.-Nr. 232208      208 liter        drum Art.-Nr. 232100      Container        IBC
------------------	--

## Technical Data:

Data	Unit	Method	EUROLUB Lowcargo SAE 5W/30
Density at 15°C	kg/L	D 4052	0,858
Viscosity at 40°C	cSt	D 445	70,20
Viscosity at 100°C	cSt	D 445	11,60
Viscosityindex (VI)		D 2270	160
Flash point (COC)	°C	D 92	235
Pourpoint	°C	D 6892	-44

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.