

EUROLUB MULTIMAX LFD3 10W-40

Description / Applications:	This lubricant has mainly been developed for heavy diesel engines even under the toughest operation conditions and all the year round. This product is very suitable for Euro 3, Euro 4 and Euro 5 engines in combination with different diesel fuel qualities. This engine oil is also suitable for application in engines with or without exhaust catalyts.
------------------------------------	---

Can be used with:	ACEA E7 API CF MB 228.5 MAN M 3277 Volvo VDS-3 Scania LDF-3 / LDF-2 / LDF Mack EO-N DAF Extended Drain Renault VI RLD-2 / RLD / RXD Deutz III-10 MTU Type 3
--------------------------	---

Delivery:	Art.-Nr. 239020	20 liter	plastic can
	Art.-Nr. 239060	60 liter	hobbock
	Art.-Nr. 239208	208 liter	drum
	Art.-Nr. 239100	Container	IBC

Technical Data:			
Data	Unit	Method	EUROLUB MULTIMAX LFD3 10W-40
Density at 15°C	kg/L	D 4052	0,860
Viscosity at 40°C	cSt	D 445	90,4
Viscosity at 100°C	cSt	D 445	13,6
Viscosityindex (VI)		D 2270	152
Flash point (COC)	°C	D 92	236
Pourpoint	°C	D 6892	-27

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 24.08.2020, made 18.04.2018
	Referenz: R20120, 19.02.2018
	Name: 239xxx_TDS_EN
	Seite 1 von 1