## PRODUCT INFORMATION



## **EUROLUB WIV ECO PRO 5W-30**

Description/Applications:	This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00	
	requirements, in practice also called VW Longlife III oils.	

Can be used with:	ACEA C3	
	API SP	
	VW 504.00 / 507.00	
	MB 229.31 / 229.51 / 229.52	
	BMW Longlife-04	
	Porsche C30	

Delivery:	ArtNr. 254005	4 x 5 Liter	can
	ArtNr. 254020	20 Liter	can
	ArtNr. 254060	60 Liter	hobbock
	ArtNr. 254208	208 Liter	drum
	ArtNr. 254100	Container	IBC

Technical Data:				
Data	Unit	Method	EUROLUB WIV ECO PRO 5W-30	
Density at 15°C	kg/L	D 4052	0,848	
Viscosity at 40°C	cSt	D 445	69,80	
Viscosity at 100°C	cSt	D 445	12,30	
Viscosityindex (VI)		D 2270	176	
Flash point (COC)	°C	D 92	224	
Pourpoint	°C	D 6892	-42	

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

 EUROLUB GmbH
 print: 10.08.2021, made 10.05.2021

 Freisinger Strasse 25-27
 Referenz: ST0656, 10.05.2020

 85386 Eching / Germany
 Name: 254xxx\_TDS\_EN

 Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20
 Seite 1 von 1

 www.eurolub.com, info@eurolub.com
 Seite 1 von 1