

EUROLUB GASMOTORENÖL HGM PLUS 40

Description/Applications:	<p>HGM PLUS 40 is a gas engine oil with high sulfated ash content. The good alkalinity protects against a rapid acidification of the engine oil and can therefore lead to longer oil life, to the knowledge of oil investigation.</p> <p>HGM Plus 40 is designed for stationary gas engines in operation with sewage gas, landfills and biogas plants even under demanding conditions.</p> <ul style="list-style-type: none"> • Good oil service life through high oxidation stability • Good lubrication and wear protection • High engine cleanliness • Good neutralization capacity • Protects against deposits • Protection against rust and corrosion
----------------------------------	--

Can be used with:	<p>API CF MAN M 3271-4 GE Jenbacher TA 1000-1109 MWM/Cat Waukesha Wärtsila Perkins Ruston</p>
--------------------------	---

Delivery:	<table> <tr> <td>Art.-Nr. 304020</td> <td>20 Liter</td> <td>plastic canister</td> </tr> <tr> <td>Art.-Nr. 304060</td> <td>60 Liter</td> <td>hobbock</td> </tr> <tr> <td>Art.-Nr. 304208</td> <td>208 Liter</td> <td>drum</td> </tr> <tr> <td>Art.-Nr. 304100</td> <td>Container</td> <td>800 – 3.000 Liter per destination</td> </tr> </table>	Art.-Nr. 304020	20 Liter	plastic canister	Art.-Nr. 304060	60 Liter	hobbock	Art.-Nr. 304208	208 Liter	drum	Art.-Nr. 304100	Container	800 – 3.000 Liter per destination
Art.-Nr. 304020	20 Liter	plastic canister											
Art.-Nr. 304060	60 Liter	hobbock											
Art.-Nr. 304208	208 Liter	drum											
Art.-Nr. 304100	Container	800 – 3.000 Liter per destination											

PRODUCT INFORMATION



Technical Data:			
Data	Unit	Method	EUROLUB GASMOTORENÖL HGM PLUS 40
Density at 15°C	kg/L	D 1298	0,892
Viscosity at 40°C	mm ² /s	D 445	135
Viscosity at 100°C	mm ² /s	D 445	13,5
Pourpoint	°C	D 97	-21
base number (TBN)	mgKOH/g	D 2896	9,0
Sulfate ash content	%	D 874	0,85

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 24.08.2020, made 04.03.2019
	Referenz: Smiha, 01.02.2019
	Name: 304xxx_TDS_EN
	Seite 2 von 2