

EUROLUB 2 TZ SELF MIX

Description / Applications:	<p>2 TZ mineral SELF MIX is a self-mixing two-stroke engine oil. 2 TZ mineral SELF MIX is recommended by the manufacturer's instructions for mixing ratios up to 1:50 and for separate lubrication (autolube systems). This two-stroke engine oil for High power engines is mineral oil based.</p>
------------------------------------	--

Can be used with:	API TC
--------------------------	--------

Delivery:	Art.-Nr. 306001	12 x 1 Liter	bottle
	Art.-Nr. 306020	20 Liter	can
	Art.-Nr. 306060	60 Liter	hobbock
	Art.-Nr. 306208	208 Liter	drum
	Art.-Nr. 306100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB 2TZ SELF MIX
Density at 15°C	kg/L	D 4052	0,879
Viscosity at 40°C	cSt	D 445	67,4
Viscosity at 100°C	cSt	D 445	9,5
Viscosityindex (VI)		D 2270	115
Flash point (COC)	°C	D 92	119
Pourpoint	°C	D 6892	-9

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 24.08.2020, made 20.11.2018
	Referenz: NSA1301, 02.08.2018
	Name: 306xxx_TDS_EN
	Seite 1 von 1