

## EUROLUB 4TZ PREMIUM 10W-40

<b>Description/Applications:</b>	<p>High-performance synthetic engine oil with base oils. Developed specifically for use in 4-stroke motorcycles with wet-running oil bath clutches.</p> <p>Its exceptionally high level of performance is achieved through the interaction of this special base oil composition and the advanced additives.</p> <ul style="list-style-type: none"> <li>• Excellent clutch performance; meets the stringent JASO MA2 requirements.</li> <li>• High level of oxidation protection by means of selected base oils and special additives.</li> </ul>
----------------------------------	--

<b>Can be used with:</b>	JASO MA2 API SN
--------------------------	--------------------

<b>Delivery:</b>	Art.-Nr. 313001	12 x 1 Liter	bottle
	Art.-Nr. 313020	20 Liter	can
	Art.-Nr. 313060	60 Liter	hobbock
	Art.-Nr. 313208	208 Liter	drum
	Art.-Nr. 313100	Container	IBC

<b>Technical Data:</b>			
<b>Data</b>	<b>Unit</b>	<b>Method</b>	<b>EUROLUB 4TZ PREMIUM 10W-40</b>
Density at 15°C	kg/L	ASTM D 7042	0,867
Viscosity at 40°C	cSt	ASTM D 7042	98,0
Viscosity at 100°C	cSt	ASTM D 7042	14,4
Viscosityindex (VI)		ASTM D 7042	154
Flash point (COC)	°C	DIN ISO 2592	226
Pourpoint	°C	DIN ISO 3016	-30

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 D-85386 Eching - Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 40 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	print: 02.03.2022, made: 20.11.2018
	reference: R20049, 18.10.16
	name: 313xxx_TDS_EN.docx
	page 1 of 1