

EUROLUB GTS 20W-50

Description/Applications:	It is a multigrade oil, which meet all requirements of spark-ignition petrol or diesel engines. The adjustable viscosities guarantee good lubrication under all operating conditions.
----------------------------------	---

Can be used with:	API CH-4 / CF-4 / SJ ACEA A3/B3, E2 MB 228.1, MB 229.1 MAN 271 Volvo VDS CAT TO2 Allison C-4
--------------------------	--

Delivery:	Art.-Nr. 325001	12 x 1 Liter	bottle
	Art.-Nr. 325004	4 x 4 Liter	can
	Art.-Nr. 325005	4 x 5 Liter	can
	Art.-Nr. 325018	18 Liter	canister
	Art.-Nr. 325020	20 Liter	canister
	Art.-Nr. 325060	60 Liter	hobbock
	Art.-Nr. 325208	208 Liter	drum
	Art.-Nr. 325100	Container	IBC 1.000L

Technical data:

Data	Unit	Method	EUROLUB GTS 20W-50
Density at 15°C	kg/L	ASTM D 4052	0,884
Viscosity at 40°C	cSt	ASTM D 445	152
Viscosity at 100°C	cSt	ASTM D 445	16,72
Viscosityindex (VI)		ASTM D 2270	118
Flash point (COC)	°C	ASTM D 92	254
Pourpoint	°C	ASTM D 6892	-27

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.