

EUROLUB HYDROFLUID UTTO

| | |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description / Applications: | This universal tractor transmission oil (UTTO) has been developed for the hydraulics and transmissions of most generally used agricultural and road-construction equipment. |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

| | | |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| Can be used with: | API GL-4 Ford M2C-134-D John Deere JDM, J20C Massey Ferguson M1135 / M1141 / M1143 / M1145 Cat TO-2 Case MS1207 / MS1209 / MS1210 / MS 1230 / MS1317 ZF TE-ML 03E / 05F / 06K / 17E | Volvo WB 101 Allison C4 |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|

| | | | |
|------------------|-----------------|-----------|---------|
| Delivery: | Art.-Nr. 329020 | 20 Liter | can |
| | Art.-Nr. 329060 | 60 Liter | hobbock |
| | Art.-Nr. 329208 | 208 Liter | drum |
| | Art.-Nr. 329100 | Container | IBC |

Technical Data:

| Data | Unit | Method | EUROLUB Hydrofluid UTTO |
|---------------------|------|--------------|-------------------------|
| Density at 15°C | kg/L | DIN 51 757 | 0,873 |
| Viscosity at 40°C | cSt | DIN 51 562 | 62,0 |
| Viscosity at 100°C | cSt | DIN 51 562 | 12,3 |
| Viscosityindex (VI) | | DIN ISO 2909 | 140 |
| Flash point (COC) | °C | DIN ISO 2592 | 220 |
| Pourpoint | °C | DIN ISO 3016 | -36 |

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

| | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|
| EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com | print: 24.08.2020, made 26.04.2018 |
| | Referenz: 150222PEN, 01.01.2019 |
| | Name: 329xxx_TDS_EN |
| | Seite 1 von 1 |