

EUROLUB UNI TRUCK STOU 10W-40

Description/Applications:	<p>An up-to-date multifunctional oil for agricultural and earthmoving equipment, formulated with top-grade solvent refined and base oils and additives, to achieve the following properties: - a powerful dispersion and detergency - a high activity against wear, corrosion and foam - a very strong resistance to oxidation - an excellent extreme pressure properties - a high and stable viscosity index</p> <p>This multifunctional lubricant (*) has been developed to achieve one single lubricating oil that is able to lubricate: - gasoline engines - diesel engines (with or without turbo-charging) - transmissions (also "wet" brakes) - hydraulic systems (*) a so-called Super Tractor Oil Universal=STOU</p>
----------------------------------	---

Can be used with:	<p>ACEA E3/E2 HLP-D/HVLP-D Allison C-4 Massey Ferguson CMS M1145 / M 1144 ZF TE-ML 03A/05K/06B/06C/07B/07D</p>	<p>API SF/CG-4/GL-4 ISO-VG 32-100 NH 410B Cat TO-2</p>
--------------------------	--	--

Delivery:	<p>Art.-Nr. 330020 20 Liter canister Art.-Nr. 330060 60 Liter hobbock Art.-Nr. 330208 208 Liter drum Art.-Nr. 330100 Container IBC 1.000L</p>
------------------	---

Technical Data:

Data	Unit	Method	EUROLUB UNI TRUCK STOU 10W-40
Density at 15°C	kg/L	ASTM D 4052	0,870
Viscosity at 40°C	cSt	ASTM D 445	85,8
Viscosity at 100°C	cSt	ASTM D 445	13,10
Viscosityindex (VI)		ASTM D 2270	152
Flash point (COC)	°C	ASTM D 92	220
Pourpoint	°C	ASTM D 6892	-45

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print 24.08.2020, made 20.11.2018
	Referenz: 150095pen, 01.10.2017
	Name: 330xxx_TDS_EN
	Seite 1 von 1