

EUROLUB HD 4C 40

Description / Application:	HD 4C 40 is a purpose powerful monograde oil. The range of services covers the requirements of Diesel engines with and without turbocharging and gasoline engines with appropriate instructions. HD 4C 40 is suitable for use in commercial vehicle diesel engines of fleets, agricultural and construction aggregates.
-----------------------------------	---

Can be used with:	API CD/SF Caterpillar Series 3 David Brown DB OM 616 MACK EO-J MIL-L 2104 C Volvo B20
--------------------------	--

Delivery:	Art.-Nr. 334020	20 Liter	canister
	Art.-Nr. 334060	60 Liter	hobbock
	Art.-Nr. 334208	208 Liter	drum
	Art.-Nr. 334100	Container	800 – 3.000 Liter container per destination
	Art.-Nr. 334000	Bulk	ab 3.001 Liter Bulk per destination

Technical Data:			
Data	Unit	Method	EUROLUB HD 4C 40
Density at 15°C	kg/l	DIN 12 185	0,882
Viscosity at 40°C	cSt	DIN 51 562	132
Viscosity at 100°C	cSt	DIN 51 562	14,5
Viscosity Index (VI)		DIN ISO 2909	105
Flash point (COC)	°C	DIN ISO 2592	220
Pourpoint	°C	DIN ISO 3016	-27

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 24.08.2020, made 26.04.2018
	Referenz: MN3104, 01.09.2019
	Name: 334xxx_TDS_EN
	Seite 1 von 1