

EUROLUB GT 10W-40

Description/Applications:	This all-round motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. GT 10W-40 is suitable for vehicles with mileages over 100.000 km.
----------------------------------	---

Can be used with:	ACEA A3 / B4 API SL / CF MB 229.1 VW 501.01 / 505.00
--------------------------	---

Delivery:	Art.-Nr. 337001	12 x 1 Liter	bottle
	Art.-Nr. 337004	4 x 4 Liter	can
	Art.-Nr. 337005	4 x 5 Liter	can
	Art.-Nr. 337020	20 Liter	can
	Art.-Nr. 337060	60 Liter	hobbock
	Art.-Nr. 337208	208 Liter	drum
	Art.-Nr. 337100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB GT 10W-40
Density at 15°C	kg/L	D 4052	0,867
Viscosity at 40°C	cSt	D 445	98,0
Viscosity at 100°C	cSt	D 445	14,4
Viscosityindex (VI)		D 2270	154
Flash point (COC)	°C	D 92	226
Pourpoint	°C	D 6892	-30

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 10.08.2021, made 26.04.2018
	Referenz: R20259, 25.07.2019
	Name: 337xxx_TDS_EN
	Seite 1 von 1