

EUROLUB HD 4C TO-4 10W

Description / Applications:	<p>HD 4C TO-4 are special power transmission oils for the supply of construction equipment and tractors.</p> <p>HD 4C TO-4 meet the increased requirements of the Caterpillar TO-4 specification and are therefore suitable for use in transmissions, final drives, hydraulics, wet brakes and Suitable couplings that require this specification.</p> <p>This oil cannot be used in engines.</p>
------------------------------------	--

Can be used with:	<p>Cat TO-4 / TO-2 Allison C4 Komatsu KES 07.868.1</p>
--------------------------	--

Delivery:	<table> <tr> <td>Art.-Nr. 338020</td> <td>20 Liter</td> <td>canister</td> </tr> <tr> <td>Art.-Nr. 338060</td> <td>60 Liter</td> <td>hobbock</td> </tr> <tr> <td>Art.-Nr. 338208</td> <td>208 Liter</td> <td>drum</td> </tr> <tr> <td>Art.-Nr. 338100</td> <td>Container</td> <td>800 – 3.000 Liter per destination</td> </tr> <tr> <td>Art.-Nr. 338000</td> <td>Bulk</td> <td>3.001 Liter per destination</td> </tr> </table>	Art.-Nr. 338020	20 Liter	canister	Art.-Nr. 338060	60 Liter	hobbock	Art.-Nr. 338208	208 Liter	drum	Art.-Nr. 338100	Container	800 – 3.000 Liter per destination	Art.-Nr. 338000	Bulk	3.001 Liter per destination
Art.-Nr. 338020	20 Liter	canister														
Art.-Nr. 338060	60 Liter	hobbock														
Art.-Nr. 338208	208 Liter	drum														
Art.-Nr. 338100	Container	800 – 3.000 Liter per destination														
Art.-Nr. 338000	Bulk	3.001 Liter per destination														

Technical Data

Data	Unit	Method	EUROLUB HD 4C TO-4 10W
Density at 15°C	kg/l	DIN 51 757	0,878
Viscosity at 40°C	cSt	DIN 51 562	39,60
Viscosity at 100°C	cSt	DIN 51 562	6,45
Viscosityindex (VI)		DIN ISO 2909	111
Flash point (COC)	°C	DIN ISO 2592	216
Pourpoint	°C	DIN ISO 3016	-34

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 24.08.2020, made 26.04.2018
	Referenz: MN2601, 01.09.2019
	Name: 338xxx_TDS_EN
	Seite 1 von 1