

EUROLUB GEAR AXLE SB 75W-90

Description/Applications:	Light-gear oil for extended drain intervals according to specifications. Can also be used for very high mechanical and thermal stress.
----------------------------------	---

Can be used with:	API GL-4/GL-5/MT-1 MIL-L-2105D/MIL-PRF-2105E, SAE J2360 MB 235.8 MAN 341 Typ Z2 MAN 342 Typ S1 SCANIA STO 1:0 Volvo 97312 ZF TE-ML 02B/05A/12L/12N/16F/17B/19C/21A Meritor 076-N EATON Europe
--------------------------	--

Delivery:	Art.-Nr. 347020	20 Liter	plastic canister
	Art.-Nr. 347060	60 Liter	hobbock
	Art.-Nr. 347208	208 Liter	drum
	Art.-Nr. 347100	1.000 Liter	container

Technical Data:

Data	Unit	Method	EUROLUB GEAR AXLE SB 75W-90
Density at 15°C	kg/L	DIN 51 757	0,890
Viscosity at 40°C	mm ² /s	DIN 51 562	74,6
Viscosity at 100°C	mm ² /s	DIN 51 562	14,9
Viscosity index		DIN ISO 2909	211
Flash point	°C	ISO 2592	216
Pourpoint	°C	DIN ISO 3016	-46

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.