

EUROLUB GEAR TRANS M 75W-90

Description/Applications:	Lightrun gear oil for longer intervals. The full performance is only achieved unmixed. Optimal gear lubrication over a wide temperature range, even at very high or low outside temperatures. Good protection of bearings and gears in heavy use at high loads.
----------------------------------	--

Can be used with:	API GL-4 MB 235.11 MAN 341 Typ Z2/E1 ZF TE-ML 16A/17A/19A/19C
--------------------------	--

Delivery:	Art.-Nr. 348020 20 Liter plastic canister Art.-Nr. 348060 60 Liter hobbock Art.-Nr. 348208 208 Liter drum
------------------	---

Technical Data:			
Data	Unit	Method	EUROLUB GEAR TRANS M 75W-90
Density at 15°C	kg/L	DIN 51 757	0,877
Viscosity at 40°C	mm ² /s	DIN 51 562-1	116,7
Viscosity at 100°C	mm ² /s	DIN 51 562-1	18,3
Viscosity Index (VI)		DIN ISO 2909	175
Flash point (COC)	°C	DIN ISO 2592	182
Pourpoint	°C	DIN ISO 3016	-42

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print 22.09.2020, made 26.11.2018
	Referenz: NSA1713, 170418
	Name: 348xxx_TDS_EN
	Seite 1 von 1