

EUROLUB GEAR EP-DB 85W-140

Description / Applications:	GEAR EP-DB 85W-140 is for very highly loaded hypoid geared drive axles as well as cone and spur gears, steering gear and non-synchronized transmissions in motor vehicles and working machines aligned.
------------------------------------	---

Can be used with:	API GL-5 MIL PRF – 2105D
--------------------------	-----------------------------

Delivery:	Art.-Nr. 364020	20 Liter	can
	Art.-Nr. 364060	60 Liter	hobbock
	Art.-Nr. 364208	208 Liter	drum
	Art.-Nr. 364100	1000 Liter	IBC

Technical Data:			
Data	Unit	Method	EUROLUB GEAR EP-DB 85W-140
Density at 15°C	kg/L	ASTM D 4052	0,901
Viscosity at 40°C	cSt	ASTM D 445	385
Viscosity at 100°C	cSt	ASTM D 445	26,8
Viscosityindex (VI)		ASTM D 2270	94
Flash point (COC)	°C	ASTM D 92	236
Pourpoint	°C	ASTM D 6892	-18

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 10.08.2021, made 01.02.2018
	Referenz: SwioHL5, 01.02.2019
	Name: 364xxx_TDS_EN
	Seite 1 von 1