

EUROLUB GEAR FLUIDE 15 BM

Description/Applications:	Low-Viscosity ATF for maximum fuel economy potential. Adapted to the requirements of Mercedes-Benz 7-speed automatic transmissions from 06/2010. Colour: blue
----------------------------------	--

Can be used with:	MB 236.15 MB 722.9 NAG2FE+ SSANGYONG
	MB 001 989 77 03

Delivery:	Art.-Nr. 366001	12 x 1 Liter	bottle
	Art.-Nr. 366020	20 Liter	canister
	Art.-Nr. 366060	60 Liter	hobbock
	Art.-Nr. 366208	208 Liter	drum
	Art.-Nr. 366100	Container	IBC 1.000L

Technical Data:			
Data	Unit	Method	EUROLUB GEAR FLUIDE 15 BM
Density at 15°C	kg/L	ASTM D 4052	0,834
Viscosity at 40°C	cSt	ASTM D 445	21,5
Viscosity at 100°C	cSt	ASTM D 445	4,98
Viscosityindex (VI)		ASTM D 2270	168
Flash point (COC)	°C	ASTM D 92	220
Pourpoint	°C	ASTM D 6892	-55

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 D-85386 Eching - Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 22.09.2020, made: 28.11.2018
	reference: MN8215, 01.09.2019
	name: 366xxx_TDS_EN
	page 1 of 1