

EUROLUB GEAR UNI HC 80W-90

Description / Applications:	GEAR UNI HC 80W-90 is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product widely usable.
------------------------------------	---

Can be used with:	API GL-3 / GL-4 / GL-5 API MT-1 MIL-L-2105D / MIL-PRF-2105 E, SAE J2360 DAF MAN 341 Typ Z2 / MAN 342 Typ M2 Scania STO 1:0 ZF TE-ML 02B / 04G / 05A / 07A / 12L / 12M ZF TE-ML 16B / 16C / 17H / 19B / 21A MB 235.0 Mack GO-J Iveco
--------------------------	---

Delivery:	Art.-Nr. 367020	20 Liter	can
	Art.-Nr. 367060	60 Liter	hobbock
	Art.-Nr. 367208	208 Liter	drum
	Art.-Nr. 367100	1000 Liter	IBC

Technical Data:			
Data	Unit	Method	EUROLUB GEAR UNI HC 80W-90
Density at 15°C	kg/L	ASTM D 4052	0,890
Viscosity at 40°C	cSt	ASTM D 445	146,4
Viscosity at 100°C	cSt	ASTM D 445	15,2
Viscosityindex (VI)		ASTM D 2270	105
Flash point (COC)	°C	ASTM D 92	200
Pourpoint	°C	ASTM D 6892	-30

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	Druckdatum: 24.08.2020, erstellt am 01.02.2018
	Referenz: NSA1808, 16.04.2018
	Name: 367xxx_TDS_EN
	Seite 1 von 1