

EUROLUB GEAR FLUIDE CVT

Description / Applications:	GEAR FLUIDE CVT is designed for application in continuously variable automatic gear boxes. The so called CVTF's. Colour: yellow
------------------------------------	--

Can be used with:	<p>MB 236.20 Hyundai/Kia SP-III Mazda CVT Fluid JWS 3320 VW G 052-180 (TL 521 80) BMW CVT EZL 799A Mini Cooper EZL 799A Ford CVT WSS M2C928-A/M2C933-A Ford CVT Fluid 23/30/MERCON C MOPAR CVTF +4 Chrysler/Jeep CVT Fluid NS-2 GM/Saturn DEX-CVT Daihatsu AMMIX CVT Fluid DC Honda HMMF/HCF-2 Mitsubishi Diaqueen CVT Fluid J1/J4 Mitsubishi Diaqueen ATF SP-III Toyota CVT Fluid TC/CVT Fluid FE Nissan CVT Fluid NS-1/NS-2/NS-3 Subaru CVT oil for LINEARTRONIC Subaru SCVT Fluid/CVT Oil/CVT Fluid Green 1/NS-2/GREEN 2 Subaru i-CVT Fluid / i-CVT Fluid FG</p>
	<p>Audi G052 180 A2 Audi G052 516 A2 Fiat CVT 75W80 Dodge NS-2/CVTF4 Ford WSS-M2C933-A Honda 08260-99905HE MB 001 989 46 03 Mini (BMW) 83 22 2 344 207 Toyota 08886-02505 Honda 082609995HE MB 001 989 46 03 Toyota 08886-02505</p>

PRODUCT INFORMATION



Delivery:	Art.-Nr. 368001	12 x 1 Liter	bottle
	Art.-Nr. 368020	20 Liter	can
	Art.-Nr. 368060	60 Liter	hobbock
	Art.-Nr. 368208	208 Liter	drum
	Art.-Nr. 368100	1000 Liter	IBC

Technical Data:

Data	Unit	Method	EUROLUB Gear Fluide CVT
Density at 15°C	kg/L	ASTM D 4052	0,852
Viscosity at 40°C	cSt	ASTM D 445	36,63
Viscosity at 100°C	cSt	ASTM D 445	7,02
Viscosityindex (VI)		ASTM D 2270	156
Flash point (COC)	°C	ASTM D 92	210
Pourpoint	°C	ASTM D 6892	-45

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 10.08.2021, made 31.01.2018
	Referenz: MN8216, 01.09.2019
	Name: 368xxx_TDS_EN
	Seite 2 von 2