

## EUROLUB GEAR FLUIDE 6

<b>Description/Applications:</b>	<p>This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF is required, which exceeds ATF Dexron III and II. Its special composition causes a longer lifetime of this liquid compared with older Dexron types. This product cannot be used in DCT's and CVT's or when an oil with the Ford Type F/G specification is recommended.</p> <p>Colour: red</p>
<b>Can be used with:</b>	<p>Aisin Warner JWS 3309(T-IV)/3324(WS)/AW-1                  Allison C3/C4, BMW 7045E/8072B/LA2634/Mini C T-IV                  Cat TO-2, Chrysler Dodge Mopar AS68RC/69RC (T-IV)                  Chrysler ATF+ /+2/+3/+4, Fiat Type IV                  Daihatsu ATF D-II/D-III SP                  Ford Mercon LV/Mercon/M2C138-CJ/166-H/922-A1/924-A                  GM Dexron VI/II/IID/IIE/IIIG/IIIH, TASA                  Honda Acura DW-1/ATF-Z1(except in CVT)                  Hyundai/Kia SP-II/SP-III/SP-IV/SP-IV M/SP-IV RR                  Hyundai/Kia JWS 3314/9683, Isuzu ATF II/III/SP                  Jaguar ATF 3403 M115/JLM 20238/20292                  JASO M315-2013 1A/1A-LV/2A                  Mazda ATF DII/M-III/M-V/FZ/F-1/S-1/N-1/3317                  MB 236.1/2/3/236.5/236.7/236.8/236.9/236.41                  Mitsubishi SK/SP-II/SP-III/SP-IV/AW/J2/J3/ATF PA                  Nissan Matic C/D/J/K/S, Porsche ATF 3403-M115/T-IV                  Subaru ATF ATF/AW-1/5AT/ATF HP                  Suzuki ATF 3309/3314/3317/2326/2384K                  Toyota D-II/D-III/T-III/T-IV/WS                  VAG G-052-025/052-055/052-162/052-990                  VAG G-053-025/055-025/055-162/055-540/060-162                  Voith 55.6335.xx (G607), Volvo 97335/97340/1161540                  ZF 5HP 18FL/19FL/24A/30/4HP20, ML 05L/09/11A/B/21L</p>
	<p>BMW 83 22 0 397 114                  GM 93165414                  MB 001 989 69 03                  Opel 19 40 184                  Vauxhall 93165414</p>

<b>Delivery:</b>	Art.-Nr. 370001	12 x 1 Liter	bottle
------------------	-----------------	--------------	--------

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	print: 10.08.2021, made 26.11.2018
	Referenz: STA2112, 130418
	Name: 370xxx_TDS_EN
	Seite 1 von 2

# PRODUCT INFORMATION



Art.-Nr. 370005	4 x 5 Liter	bottle
Art.-Nr. 370020	20 Liter	can
Art.-Nr. 370060	60 Liter	hobbock
Art.-Nr. 370208	208 Liter	drum
Art.-Nr. 370100	1000 Liter	IBC

## Technical Data:

Data	Unit	Method	EUROLUB Gear Fluide 6
Density at 15°C	kg/L	ASTM D 4052	0,838
Viscosity at 40°C	cSt	ASTM D 445	25,47
Viscosity at 100°C	cSt	ASTM D 445	5,55
Viscosityindex (VI)		ASTM D 2270	164
Flash point (COC)	°C	ASTM D 92	216
Pourpoint	°C	ASTM D 6892	-50

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.