

EUROLUB GEAR FLUIDE IID

Description / Applications:	GEAR FLUIDE IID may be used for automatic gearboxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID fluid is required. Colour: red
------------------------------------	---

Can be used with:	GM Dexron II D MB 236.6 / 236.7 Allison C-4 Voith 55.6335 (G607) ZF TE-ML 03D/04D/11A/14A/17C	MAN 339 Typ Z1 / V1 CAT TO-2
	BMW 81 22 9 400 272 Ford M2C-138CJ GM 90350342 MB 000 989 92 03 Opel 19 40 700 Vauxhall 90350342 Volvo 1161744	

Delivery:	Art.-Nr. 373001	12 x 1 Liter	bottle
	Art.-Nr. 373020	20 Liter	can
	Art.-Nr. 373060	60 Liter	hobbock
	Art.-Nr. 373208	208 Liter	drum
	Art.-Nr. 373100	1000 Liter	IBC

Technical Data:

Data	Unit	Method	EUROLUB GEAR FLUIDE IID
Density at 15°C	kg/L	ASTM D 4052	0,870
Viscosity at 40°C	cSt	ASTM D 445	34,9
Viscosity at 100°C	cSt	ASTM D 445	6,8
Viscosityindex (VI)		ASTM D 2270	156
Flash point (COC)	°C	ASTM D 92	166
Pourpoint	°C	ASTM D 6892	-45

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 22.09.2020, made 26.11.2018
	Referenz: MN8205, 01.09.2019
	Name: 373xxx_TDS_EN
	Seite 1 von 1