

# PRODUCT INFORMATION



## EUROLUB GEAR LS 80W~~+~~<sub>-</sub>90

<b>Description / Applications:</b>	GEAR <del>ear</del> LS 80W <del>+</del> <sub>-</sub> 90 has especially been developed for the perfect lubrication of so-called "Limited Slip" and "Auto-Locking" hypoid transmissions. Gear LS 80W <del>+</del> <sub>-</sub> 90 can be used in mixed fleets for variety reduction also in all drive axles with the requirement API GL 5.
------------------------------------	--

<b>Can be used with:</b>	API GL-5 / LS (Limited Slip) MIL-L 2105 D
--------------------------	--

<b>Delivery:</b>	Art.-Nr. 375020	20 Liter	can
	Art.-Nr. 375060	60 Liter	hobbock
	Art.-Nr. 375208	208 Liter	drum
	Art.-Nr. 375100	1000 Liter	IBC

<b>Technical Data:</b>			
Data	Unit	Method	EUROLUB GEAR <del>ear</del> LS 80W <del>+</del> <sub>-</sub> 90
Density at 15°C	kg/L	ASTM D 4052	0,892
Viscosity at 40°C	cSt	ASTM D 445	159,6
Viscosity at 100°C	cSt	ASTM D 445	16,3
Viscosityindex (VI)		ASTM D 2270	107
Flash point (COC)	°C	ASTM D 92	210
Pourpoint	°C	ASTM D 6892	-33

hat formatiert: Schriftart: Calibri

hat formatiert: Schriftart: Calibri

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591-0, Fax +49 81659591 - 20 Tel. 08165 / 95 91 - 0, Fax 08165 / 95 91 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	print 10.08.2021,made 26.11.2018
	Referenz: MN8106, 01.09.2019
	Name: 375xxx_TDS_EN
	Seite 1 von 1