

## EUROLUB GEAR FLUIDE 8G

<b>Description / Applications:</b>	<p>GEAR FLUIDE 8G is specially formulated for the lubrication of ZF 8HP transmissions. The oil contributes greatly to realizing fuel saving and can be used amongst others in the ZF 8HP transmissions 8HP45, 8HP55, 8HP70 and 8HP90. It can also be used in certain ZF 6HP transmissions, which are used in various VAG models.</p> <p>Colour: green</p>
------------------------------------	---

<b>Can be used with:</b>	<p>VAG G 060 162 BMW 8322 2152426 Land Rover LR023288/LR023289 ZF S671 090 310/311/312</p>
	<p>Audi G 60 162 A2 BMW 83 22 2 289 720 Chrysler 68157995AA Jaguar 02JDE26444 Land Rover LR 023288 VW G 060 162 A2</p>

<b>Delivery:</b>	Art.-Nr. 376001	12 x 1 Liter	bottle
	Art.-Nr. 376020	20 Liter	can
	Art.-Nr. 376060	60 Liter	hobbock
	Art.-Nr. 376208	208 Liter	drum
	Art.-Nr. 376100	1000 Liter	IBC

### Technical Data:

Data	Unit	Method	EUROLUB GEAR FLUIDE 8G
Density at 15°C	kg/L	ASTM D 4052	0,830
Viscosity at 40°C	cSt	ASTM D 445	29,8
Viscosity at 100°C	cSt	ASTM D 445	5,99
Viscosityindex (VI)		ASTM D 2270	152
Flash point (COC)	°C	ASTM D 92	218
Pourpoint	°C	ASTM D 6892	-50

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	made: 22.09.2020, made 31.01.2018
	Referenz: MN8213, 11.09.2019
	Name: 376xxx_TDS_EN
	Seite 1 von 1