

EUROLUB GEAR FLUIDE III

Description / Applications:	GEAR FLUIDE III may be used for automatic gearboxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID, IIE, IIIF, IIIG or IIIH fluid is required. Colour: red
------------------------------------	--

Can be used with:	GM Dexron IID / IIE / IIIF / IIIG / IIIH MB 236.1 / 236.5 / 236.6 / 236.7 / 236.9 Ford Mercon M2C138-CJ/166H MAN 339 Z1/V1 Allison C4/TES-389 CAT TO-2 Volvo 97341 Voith 55.6335 (G607) ZF TE-ML 02F/03D/04D/09A/09B/11A/11B/14A/17C
	Acura 52107891AA Ford 1 565 889 Ford A97SXM2C202AB MAN 339 V1 MB 001 989 21 03 Mini (BMW) 83 22 9 407 860 Peugeot 9730.AE Volvo 1161521 VW G 052 533 A2

Delivery:	Art.-Nr. 378001	12 x 1 Liter	bottle
	Art.-Nr. 378020	20 Liter	can
	Art.-Nr. 378060	60 Liter	hobbock
	Art.-Nr. 378208	208 Liter	drum
	Art.-Nr. 378100	1000 Liter	IBC

PRODUCT INFORMATION



Technical Data:

Data	Unit	Method	EUROLUB Gear Fluide III
Density at 15°C	kg/L	ASTM D 4052	0,851
Viscosity at 40°C	cSt	ASTM D 445	37,7
Viscosity at 100°C	cSt	ASTM D 445	7,6
Viscosityindex (VI)		ASTM D 2270	175
Flash point (COC)	°C	ASTM D 92	210
Pourpoint	°C	ASTM D 6892	-51

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.