

## EUROLUB GEAR FLUIDE V-FE

### Description / Applications:

A very high graded automatic transmission fluid formulated with a number of special selected base oils and additives to obtain the following properties:

- a high shifting comfort
- a very low pour point
- very good stability against oxidation
- very good thermal properties
- a positive activity against wear, corrosion and foam
- a constant friction stability ensuring perfect clutch operation
- a perfect compatibility with seals and non-ferro metals
- extremely resistant against shudder vibration
- as a result of the perfect viscosity grade a fuel-efficiency potential
- Colour: red

### Can be used with:

AISIN WARNER JWS 3309  
 JASO M315 Type 1A  
 JATCO ATF  
 JATCO 3100 PL085  
 Toyota ATF Type T/T-II/T-III/T-IV  
 Nissan/INFINITI MATIC D/J/K  
 Mitsubishi Diamond SP-II/SP-III  
 Mazda ATF-M III / ATF-MV  
 Daihatsu Alumix ATF MULTI  
 Honda ATF-Z1 (not for CVT) / ATF DW-1  
 Suzuki 3313, 3317, 2384K  
 Suzuki ATF OIL / ATF OIL SPECIAL  
 Subaru ATF / ATF-HP  
 Hyundai/Kia SP-II/SP-III  
 GM Dexron IID/IIIH  
 Chrysler ATF +3/+4  
 VW G052 025-A2 / G052 162-A1 / G 052 990-A1 / G055 025-A1/A2  
 BMW 7045E / ETL-8072B / LA2634 / LT71141  
 MB 236.1/2/3/5/6/7/9/10/11  
 Porsche JWS 3309  
 Volvo 97340/97341  
 VOITH 55.6335  
 Allison C-4  
 ZF TE-ML 03D/04D/11B/14A/14B/16L/17  
 Ford MERCON V  
 MAN 339F/V1/V2/Z1/Z2

# PRODUCT INFORMATION



	Audi G 052 162 A2 BMW 83 22 2 305 395 Citroen Z 000169756 GM 90513486 Jaguar JLM 20238 MB 001 989 22 03 Mini (BMW) 83 22 9 407 858 Opel 19 40 707 Peugeot 9736.22 Porsche 000 043 207 00 Seat G 052 162 A2 Skoda G 052 162 A2 Vauxhall 90513486 VW G 052 162 A2
--	--

<b>Delivery:</b>	Art.-Nr. 379001	12 x 1 Liter	bottle
	Art.-Nr. 379020	20 Liter	plastic canister
	Art.-Nr. 379060	60 Liter	hobbock
	Art.-Nr. 379208	208 Liter	drum
	Art.-Nr. 379100	Container	800 – 3.000 Liter per destination

<b>Technical Data:</b>			
<b>Data</b>	<b>Unit</b>	<b>Method</b>	<b>EUROLUB GEAR FLUIDE V-FE</b>
Density at 15°C	kg/L	ASTM D 4052	0,844
Viscosity at 40°C	cSt	ASTM D 445	31,23
Viscosity at 100°C	cSt	ASTM D 445	6,87
Viscosity index (VI)		ASTM D 2270	189
Flash point (COC)	°C	ASTM D 92	216
Pourpoint	°C	ASTM D 6892	-48

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	print 22.09.2020, made 26.11.2018
	Referenz: MN8218, 01.09.2019
	Name: 379xxx_TDS_EN
	Seite 2 von 2