

EUROLUB GEAR FLUIDE BM SPEZIAL

Description/Applications:	<p>GEAR FLUIDE BM SPEZIAL is a fuel efficient ATF based on state-of-the-art additives and carefully selected base oils. It has been specially adapted to the requirements of modern step type automatic transmissions.</p> <p>Its high friction level provides almost slip free high torque transmission rates and provides spontaneous and sporty shifting operation. Its excellent friction retention provides stable shift performance during the whole drain interval.</p> <p>Colour: yellow</p>		
Can be used with:	<p>VW G 055005 A1/A2/A6 BMW 1375.4 (83220142516/83220144137) Ford Mercon SP/LV Jaguar C2C 8432 Land Rover TYK500050 Hyundai 040000C90SG ZF S671 090 252/253/255</p>		
	<p>Aston Martin 4G4316A509 Audi G 055 005 A2 Bentley PY112995PA BMW 83 22 0 144 137 Hyundai 040000C90SG Jaguar C2C 8432 Land Rover TYK5000050 Maserati 231603 Porsche M-1375.4 Rolls Royce M-1375.4 VW G 055 005 A2</p>		
Delivery:	<p>Art.-Nr. 381001 Art.-Nr. 381020 Art.-Nr. 381060 Art.-Nr. 381208 Art.-Nr. 381000</p>	<p>12 x 1 Liter 20 Liter 60 Liter 208 Liter 1.000 Liter</p>	<p>plastic bottle plastic canister hobbock drum IBC</p>

PRODUCT INFORMATION



Technical Data:

Data	Unit	Method	EUROLUB GEAR FLUIDE BM SPEZIAL
Density at 15°C	kg/L	ASTM D 4052	0,850
Viscosity at 40°C	cSt	ASTM D 445	32,0
Viscosity at 100°C	cSt	ASTM D 445	6,6
Viscosityindex (VI)		ASTM D 2270	167
Flash point (COC)	°C	ASTM D 92	214
Pourpoint	°C	ASTM D 6892	-52

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.