

EUROLUB GEAR ECO 75W-80

Description / Application:	<p>Smooth running gear oil with lowered cold viscosity for good fuel efficiency. Developed for wear protection and cold-shift requirements in modern passenger car manual transmissions.</p> <p>It is used in modern passenger car manual transmissions.</p> <p>The lowered viscosity and optimized viscosity-temperature behavior allow a reduction in fuel consumption, while at the same time providing comfortable shifting behavior and low shifting forces.</p>
-----------------------------------	---

Can be used with:	<p>API GL-4 API GL-5 BMW MTF LT-1/-2/-3/-4 Fiat 9.55550-MZ2 Ford WSS-M2C-200-D2 MB 235.10 PSA 9730 A2/A8/B71 2330 Toyota JWS 227 VW G 009 317 VW G 052 171 VW G 052 178 VW G 052 512 VW G 052 532 VW G 052 527 VW G 052 726 VW G 052 798 VW G 055 726</p>
	<p>Audi G 052 171 A2 Audi G 052 911 A2 BMW 83 22 0 309 031 Citroen B71 2330 Citroen 9734.S2 Fiat 9.55550 MZ1 GM 90540998 MB 001 989 26 03 Opel 19 40 182 Peugeot B712330 Seat G 052 911 Seat G 052 171 A2 Skoda G 052 911 Skoda G 052 171 A2 Volvo 97308</p>

PRODUCT INFORMATION



	Volvo 31280771 VW G 052 145 A1 VW G 052 171 A2
--	--

Delivery:	Art.-Nr. 386001	12 x 1 Liter	bottle
	Art.-Nr. 386020	20 Liter	can
	Art.-Nr. 386060	60 Liter	hobbock
	Art.-Nr. 386208	208 Liter	drum
	Art.-Nr. 386100	Container	IBC

Technical Data:			
Data	Unit	Method	EUROLUB GEAR ECO SAE 75W/80
Density at 15°C	kg/L	D 4052	0,876
Viscosity at 40°C	cSt	D 445	57,9
Viscosity at 100°C	cSt	D 445	9,5
Viscosityindex (VI)		D 2270	145
Flash point (COC)	°C	D 92	215
Pourpoint	°C	D 6892	-42

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 22.09.2020, erstellt am 03.03.2020
	Referenz: M8104, 12.03.2019
	Name: 386xxx_TDS_EN
	Seite 2 von 2