

EUROLUB CLP ISO-VG 100

Category:	Industrial gear oil		
Application:	CLP is formulated with excellent base oils and state-of-the-art additive technology. Effective ingredients ensure optimum lubrication and long-lasting protection against aging. Gear oils are used to lubricate face, bevel and worm gears, gear drives and bearings with immersion and recirculating lubrication, as well as for jaw clutches, thrust bearings of roll necks and highly loaded sliding surfaces (joints).		
Can be used with_	DIN 51 517 / part 3 FZG-Test A8, 3/90 Schadenskraftstufe: >12 AIST 224 (US Steel) AGMA 9005 E02 (EP)		
Delivery:	Art.-Nr. 413020	20 Liter	plastic canister
	Art.-Nr. 413060	60 Liter	Hobbock
	Art.-Nr. 413208	208 Liter	Drum
	Art.-Nr. 413100	Container	800 – 3.000 Liter per Destination

Technical Data:			
Data	Unit	Method	EUROLUB CLP ISO-VG 100
Density at 15°C	g/cm ³	DIN 51 757	0,881
Viscosity at 40°C	mm ² /s	DIN 51 562	102
Viscosity at 100°C	mm ² /s	DIN 51 562	11,2
Flash point (COC)	°C	DIN ISO 2592	245
Pourpoint	°C	DIN ISO 3016	-21

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.de , info@eurolub.de	print: 24.08.2020, made 12.12.2018
	Referenz: Serso, 01.02.2018
	Name: 413xxx_TDS_EN
	Seite 1 von 1