

EUROLUB HLP-D 68

Category:	HLPD Hydraulic Fluids
------------------	-----------------------

Product Features: application:	<p>The HLPD hydraulic oils is based on paraffinic base oil and modern additive technology. Effective zinc containing components guarantee optimal lubrication and long-term protection against oxidation. During the process fine filtration is possible without the risk of losing valuable ingredients. Because of the high viscosity index the lubricating effect of the oil remains unaffected even at very high temperatures.</p> <p>Dispersant and detergent additives provide optimal dirt-removing properties and the product is especially suitable for centrally supplied machines.</p>
---	---

Recommendations:	DIN 51 524 / part 2	FZG-Test A8, 3/90 load stage: >12
	ISO VG 68	

Delivery:	Art.-Nr. 513020 20 Liter Art.-Nr. 513060 60 Liter Art.-Nr. 513208 208 Liter Art.-Nr. 513100 Container	plastic-canister hobbock Drum 800 – 3.000 Liter per destination
------------------	--	--

Technical Data:

Data	Unit	Method	EUROLUB HLP-D 68
Density at 15°C	kg/L	ASTM D 4052	0,882
Viscosity at 40°C	cSt	ASTM D 445	68
Viscosity at 100°C	cSt	ASTM D 445	8,6
Viscosityindex (VI)		ASTM D 2270	97
Flash point (COC)	°C	ASTM D 92	225
Pourpoint	°C	ASTM D 6892	-24

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.