

EUROLUB TRENNMITTEL T25

Category:	Molding and releasing fluid		
Product Features:	TRENNMITTEL T25 is a light-colored molding oil for the concrete industry made of refined mineral oils. After evaporation of the volatile liquid and water leakage from the fresh concrete ('bleedingwater'), this formulation provides low interfacial tension, creating a smooth concrete surface.		
Storage:	In the closed original container approx. 1 year.		
Application:	Eurolub Trennmittel T25 is applied to the clean and dry form with a brush or a suitable sprayer. The release agent is ready for use and must not be diluted with water, oils or solvents. In all applications, tests must be carried out, since the special local and material conditions have different influences on the release agent.		
Delivery:	Art.-Nr. 535020	20 Liter	plastic-canister
	Art.-Nr. 535060	60 Liter	hobbock
	Art.-Nr. 535208	208 Liter	drum
	Art.-Nr. 535100	1.000 Liter	container

Technical Data:			
Data:	Unit:	Method:	EUROLUB TRENNMITTEL T25
Density at 15°C	g/cm ³	DIN 51 757	0,85
Viskosity at 40°C	mm ² /s	DIN 51 562	6,35
Flash point COC	°C	DIN ISO 51376	> 160
Pour point	°C	DIN ISO 3016	< -15

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 D-85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	Print date: 24.08.2020, made 29.10.2018
	Referenz: evbtx, 0818
	Name: 535xxx_TDS_EN
	page 1 of 1