

EUROLUB SÄGEKETTENMEDIUM

Category:	Chain oil
------------------	-----------

Product Features: application:	<p>SÄGEKETTENMEDIUM is blended with excellent base oils and modern additives, tailored to a good formulation. A proven product for motor chain saws of all kinds. It is ideal for summer and winter operation.</p> <ul style="list-style-type: none"> • Reliable corrosion protection • High adhesion • Excellent low temperature properties • Reduced oil consumption • Very good cooling effect • Improved lubrication performance
---	--

Delivery:	Art.-Nr. 538005	4 x 5 Liter	plastic-canister
	Art.-Nr. 538020	20 Liter	plastic-canister
	Art.-Nr. 538060	60 Liter	hobbock
	Art.-Nr. 538208	208 Liter	Drum
	Art.-Nr. 538100	Container	800 – 3.000 Liter per destination

Technical Data:			
Data	Unit	Method	EUROLUB SÄGEKETTENMEDIUM
Density at 15°C	kg/L	ASTM D 4052	0,877
Viscosity at 40°C	cSt	ASTM D 445	95,4
Viscosity at 100°C	cSt	ASTM D 445	11,5
Viscosityindex (VI)		ASTM D 2270	102
Flash point (COC)	°C	ASTM D 92	230
Pourpoint	°C	ASTM D 6892	-24

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.de , info@eurolub.de	print: 24.08.2020, made 11.12.2018
	Referenz: pe150205/1217
	Name: 538xxx_TDS_EN
	Seite 1 von 1