

EUROLUB DOPPELKUPPLUNGSFLUID (DKG)

Description/Applications:	DOPPELKUPPLUNGSFLUID (DKG) is developed to fulfill the highest demands of modern high tech dual clutch transmissions and is particularly suitable for transmissions where clutch, synchronizer, gear set and hydraulic control system operate with the same fluid. Color: yellow as oil		
Can be used with:	VW G-052-529 / VW G-052-182 BMW 83222148578/83222148579 BMW 83220440214/83222147477 Ford WSS-M2C-936-A MB 236.21/236.25 Mitsubishi MZ320065 PSA 9734.S2 Porsche 999.917.080.00 Volvo 1161838 / 1161839		
	Audi G 052 529 A2 Audi G 055 529 A2 BMW 83 22 2 148 578 Chrysler 68044345EA Citroen 9734.S2 Ford 1 490 763 Land Rover GX73-M1R564-AA MB 001 989 85 03 Peugeot 9734.S2 Porsche 000 0 43 207 30 Seat G 052 182 A2 Seat G 055 529 A2 Skoda G 052 182 A2 Skoda G 055 529 A2 VW G 052 529 A2 VW G 055 529 A2		
Delivery:	Art.-Nr. 545001	12 x 1 Liter	bottle
	Art.-Nr. 545020	20 Liter	can
	Art.-Nr. 545060	60 Liter	hobbock
	Art.-Nr. 545208	208 Liter	drum
	Art.-Nr. 545100	Container	IBC

PRODUCT INFORMATION



Technical Data:

Data	Unit	Method	EUROLUB DKF (DKG)
Density at 15°C	kg/L	D 4052	0,850
Viscosity at 40°C	cSt	D 445	34,5
Viscosity at 100°C	cSt	D 445	7,22
Viscosityindex (VI)		D 2270	181
Flash point (COC)	°C	D 92	216
Pourpoint	°C	D 6892	-51

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.