

EUROLUB ZH-L ST HYDRAULIK-FLUID

Description/Applications:	ZH-L ST HYDRAULIK-FLUID has been developed specifically for use in central hydraulic systems subjected to high loads, power steering systems, sun roof mechanisms and shock absorbers. Its first-rate viscosity-temperature behaviour guarantees safe operation at high steady-state temperatures, as well as a sensitive response at very low temperatures. Color: green
----------------------------------	--

Can be used with:	VW TL 52146 (G 002 000/G 004 000) MB 345.0 BMW 812 29 407 758 Ford WSS-M2C204-A GM/Opel B040 0070 Fendt X 902.011.622 MAN M 3289
	Audi G 004 000 M2 BMW 83 29 0 429 576 Chrysler MS 11655b Citroen 9979.A3 DAF 1786 432 Fiat 9.55550-AG3 Ford 1 384 110 GM 93160548 Hyundai 00232-19017 Land Rover LR 003401 MAN 9.110.030.427 Mini (BMW) 83 29 0 429 576 Opel 19 40 715 Porsche 000 043 204 89 Saab 93 160 548 Seat G 004 000 M2 Skoda G 004 000 M2 Vauxhall 93160548 Volvo 30741424 VW G 004 000 M2

Delivery:	Art.-Nr. 564001	12 x 1 Liter	bottle
	Art.-Nr. 564020	20 Liter	can
	Art.-Nr. 564060	60 Liter	hobbock
	Art.-Nr. 564208	208 Liter	drum
	Art.-Nr. 564100	Container	IBC

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 29.09.2021, made: 28.11.2018
	Referenz: MN8990, 23.08.2019
	Name: 564xxx_TDS_EN
	Seite 1 von 2

PRODUCT INFORMATION



Technical Data:

Data	Unit	Method	EUROLUB ZH-L ST HYDRAULIK- FLUID
Density at 15°C	kg/L	D 4052	0,830
Viscosity at 40°C	cSt	D 445	19,9
Viscosity at 100°C	cSt	D 445	6,2
Viscosityindex (VI)		D 2270	304
Flash point (COC)	°C	D 92	216
Pourpoint	°C	D 6892	-51

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.