

EUROLUB FUNKENEROSIONSÖL MP2

section:	Spark ersosion oil
-----------------	--------------------

product Features:	Low aromatics base oil oxidation stabilizers
--------------------------	--

application of:	Funkenersosionsöl MP2 can be used for both smoothing and roughing. Funkenersosionsöl MP2 also can be used for super finishing as an application. It achieved excellent surface qualities.
------------------------	---

Delivery:	Art.-Nr. 686208	208 Liter	drum
------------------	-----------------	-----------	------

Remarks:	Water hazard class 1 (Self-assessment) ADR does not Disposal waste code 140 603 Storage at +5 to +30 ° C, stable for 6 months Classification Xn Harmful Water-polluting liquid. It must not enter the sewage system!!
-----------------	--

Technical Data:

Data:	Unit:	Method:	EUROLUB Funkenerosionsöl MP2
Density at 15°C	g/ml	DIN 51 757	0,797
Viscosity at 40°C	mm ² /s	DIN 51 562	2,30
Pourpoint:	°C	DIN 51 758	> 100
color number:		ASTM	uncoloured
aromatic content:			< 0,10

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.de , info@eurolub.de	Druckdatum: 24.08.2020, erstellt am 10.12.2018
	Referenz: zdielect100/1218
	Name: 686xxx_TDS_EN
	Seite 1 von 1