

## EUROLUB

### GEARFIT EP 00/000

GEARFIT EP 00/000 is a light green coloured, lithium saponified flow-grease, based on mineral oil.

<b>Application:</b>	GEARFIT EP 00/000 is suited for central lubricating installations of utility vehicles as well as for outside working units having long tubing.
<b>Properties:</b>	<ul style="list-style-type: none"> <li>• resistant to oxidation</li> <li>• increased capability of pressure</li> <li>• good water resistance</li> <li>• good protection against corrosion</li> </ul>

<b>Designation DIN 51502:</b>	GP 00/000 K-50
	EVOBUS 001 989 05 81
	MAN 81.495.030.015
	MB 001 989 08 51

<b>Delivery:</b>	Art.-Nr. 708900	20 x 900 g	tube
	Art.-Nr. 708005	5 kg	plastik hobbock
	Art.-Nr. 708015	15 kg	plastik hobbock
	Art.-Nr. 708025	25 kg	plastik hobbock
	Art.-Nr. 708180	180 kg	sheet metal drum

### Technical Data:

Data:	Unit:	Method:	EUROLUB GEARFIT EP 00/000
service temperature for permanent lubrication	°C		-50 to +120
Worked penetration	1/10 mm	ASTM D 217	400 to 460
Water resistance		DIN 51807 T1	1 – 90
Corrosion protection		DIN 51802	corrosion degree 0
Thickener			Li-12-hydroxystearate
Base oil viscosity at 40°C	mm <sup>2</sup> /s	ASTM D 445	approx.. 45
Flow pressure at -35°C	mbar	DIN 51805	< 60

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	Druckdatum: 22.09.2020, erstellt am 07.06.2017
	Referenz: siep7028, 01.01.2017
	Name: 708xxx_TDS_EN
	Seite 1 von 1