

EUROLUB ÖLFLECKENTFERNER

Performance / Application:	<p>Automatically cleans oil spills from floors, tanks, machinery, lifts, tools, automobiles, concrete wall and floor tiles, asphalt, etc.</p> <ul style="list-style-type: none"> • Safely removes oil stains from any surface • free of chlorinated hydrocarbons • cleans independently • fast action
-----------------------------------	---

Directions:	<p>For plastic surfaces and painted surfaces, try it on an inconspicuous spot first. Apply undiluted with a brush or rag and leave on for about 5 minutes. Then finish with a scrubber or brush. Absorb with absorbent material (cloth, wood chips). For stubborn dirt repeat the procedure. Pay attention to protection of groundwater.</p> <p>Special hint: Before use, carry out a compatibility test on an inconspicuous area of the area to be treated.</p>
--------------------	---

Delivery:	Art.-Nr. 815500	6 x 500 ml
	Art.-Nr. 815005	1 x 5 Ltr.

Technical Data:			
Data	Unit	Test method	EUROLUB ÖLFLECKENTFERNER
Density, 20°C	g/cm ³		0,785
Flash point	°C		-10
Ignition temperature	°C		410

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 24.08.2020, made: 08.10.2018
	Referenz: K414603
	name: 815xxx_TDS_EN
	Seite 1 von 1