

EUROLUB KÜHLERSCHUTZ D-40 super

KÜHLERSCHUTZ D-40 Super is a nitrite-, amine-, phosphate- and borate-free radiator protection based on ethylene glycol (ethanediol, monoethylene glycol). Contains an inhibitor package based on silicate and salts of organic acids (Si-OAT).

KÜHLERSCHUTZ D-40 Super must be diluted with water before use.

Description/Applications:	<p>KÜHLERSCHUTZ D-40 Super provides excellent protection against frost, rust and overheating for all modern engines, especially high-load aluminum engines.</p> <p>It effectively prevents corrosion and deposits in the cooling system with its important components such as cooling ducts in the cylinder head, engine block, radiator and water pump.</p> <p>Because the special benefits of using the D-40 Super Radiator Guard are limited to the use of the D-40 Super Radiator Guard alone, it is not recommended that it be mixed with other radiator protectors.</p> <p>Radiator guard D-40 Super should be mixed with water before filling into the cooling circuit (Use clean, not too hard water to condition the coolant) and use at a concentration of 35 to 55 vol%.</p>
Can be used with:	<p>VW TL 774 Ausf. G (Audi, Bentley, Lamborghini, Seat, Skoda, VW ab Baujahr 2008) Cummins CES 14603 MB 325.5, MB 325.6 MAN 324 Typ Si-OAT Deutz CC-14 Liebherr Min LH-01-COL3A AFNOR NF R15-601, AS 2108 ASTM D 3306, D 4656, D4985 SAE J 1034 BS 6580 Cummins 14603 CUNA NC 956-16, UNE 26361-8</p>
	<p>Audi G 012 A8G M1 MB 000 989 28 25 Seat G 012 A8G M1 Skoda G 012 A8G M1 Toyota 002721LLAC VW G 012 A8G M1</p>

PRODUCT INFORMATION



Delivery:	Art.-Nr. 834015	12 x 1 Liter	bottle
	Art.-Nr. 834005	4 x 5 Liter	can
	Art.-Nr. 834020	20 Liter	can
	Art.-Nr. 834060	60 Liter	hobbock
	Art.-Nr. 834208	208 Liter	drum
	Art.-Nr. 834100	Container	IBC

Water mixtures:

(Do not mix below -20 ° C, since less than 33% Antifreeze no corrosion protection is guaranteed.)

Ratio antifreeze	Ratio water	Frost protection to:
1 part	2 parts	-20°C
1 part	1,5 parts	-27°C
1 part	1 part	-37°C

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 11.04.2018, made 11.04.2018
	Referenz: g40 / 09/2017
	Name: 834xxx_TDS_EN
	Seite 2 von 2