

EUROLUB KÜHLERSCHUTZ D-65

KÜHLERSCHUTZ D-65 is a radiator protection based on ethylene glycol. It contains an inhibitor package based on silicate, phosphate and salts of organic acids (PSi-OAT coolant). It is nitrite, amine and borate free. KÜHLERSCHUTZ D-65 must be diluted with water before use.

Produkteigenschaften: Anwendung:	KÜHLERSCHUTZ D-65 protects all modern engines, especially heavy-duty aluminum engines, excellent against frost, rust and overheating. It prevents corrosion and deposition in the cooling system with the important components. Since the special application advantages of the KÜHLERSCHUTZ D-65, such as good aluminum protection and longer intervals (according to the manufacturer!) are only achieved when the KÜHLERSCHUTZ D-65 is used alone, mixing with other radiator protection agents is not recommended.
---	--

Can be used for:	VW TL 774 Ausf. L AS 2108-2004 ASTM D 3306 ASTM D 4985 CUNA NC 956-16 BS 6580: 2010 PN-C40007:2000 SAE J1034 SANS 1251:2005 China GB 29743-2013
-------------------------	--

Delivery:	Art.-Nr. 835015	12 x 1,5 Liter	plastic bottle
	Art.-Nr. 835020	20 Liter	plastic can
	Art.-Nr. 835060	60 Liter	hobbock
	Art.-Nr. 835208	208 Liter	drum
	Art.-Nr. 835100	1.000 Liter	IBC

PRODUCT INFORMATION



Water mixtures:

(Do not mix below -20 ° C, since less than 33% Antifreeze no corrosion protection is guaranteed.)

Ratio antifreeze	Ratio water	Frost protection to:
1 part	2 parts	-20°C
1 part	1,5 parts	-27°C
1 part	1 part	-37°C

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.