

EUROLUB KÜHLERSCHUTZ D-48 EXTRA

KÜHLERSCHUTZ D-48 Extra is a coolant based on ethylene glycol. It contains a hybrid inhibitor package based on silicate, borate and salts of organic acids. Also suitable for aluminum engines. It contains no nitrite, amine and phosphate, which contributes to better environmental compatibility.

Description / Applications:	<p>→ Protection against corrosion, cavitation and deposits.</p> <p>→ Foam reduction.</p> <p>For all antifreeze is valid: Use in conjunction with galvanized lines or containers is not recommended!!!</p> <p>Drain cooling system, rinse and fill with Kühlerschutz D-48 Extra and water in the ratio 1: 1 (or according to the mixing table).</p> <p>Kühlerschutz D-48 Extra ensures year-round corrosion and frost protection. It is recommended to use at least 33% by volume of D-48 Extra and 67% water by volume for safe protection down to -20 ° C. Mixtures with more than 70% by volume of Kühlerschutz D-48 Extra are not recommended.</p> <p>Kühlerschutz D-48 Extra is miscible with most ethylene glycol based coolants. For optimum anti-corrosive effect and to prevent sludge formation, a mixing ratio of 50% Kühlerschutz D-48 Extra and 50% water is recommended.</p>
------------------------------------	---

Can be used with:	<p>MAN 324 Typ NF MAN 324 Typ NF Pritarder MB 325.0 VW TL 774 Ausf. C BMW GS 94000 Jenbacher TA-Nr. 1000-0201 Liebherr Minimum LH-00-COL3A MTU MTL 5048 Opel/General Motors B 040 0240 Porsche für 924, 944, 968, 928 Saab 6901599</p> <p>AS 2108-2004 ASTM D 3306 ASTM D 4985 SAE J1034 AFNOR NF R 15-601 BS 6580: 2010</p>
	<p>Audi G 011 A8C A1 BMW 83 19 2 211 191 Ford 1 047 035</p>

PRODUCT INFORMATION



	Ford 5 016 438 GM 90297545 MB 000 989 08 25 Opel 19 40 656 Seat G 011 A8C A1 Vauxhall 19 40 656 VW G 011 A8C A1
--	---

Delivery:	Art.-Nr. 836015	12 x 1,5 Liter	bottle
	Art.-Nr. 836020	20 Liter	can
	Art.-Nr. 836060	60 Liter	hobbock
	Art.-Nr. 836208	208 Liter	drum
	Art.-Nr. 836100	1.000 Liter	IBC

Water mixtures:

(Do not mix below -20 ° C, since less than 33% Antifreeze no corrosion protection is guaranteed.)

Ratio antifreeze	Ratio water	Frost protection to:
1 part	2 parts	-20°C
1 part	1,5 parts	-27°C
1 part	1 part	-37°C

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	Druckdatum: 10.08.2021, erstellt am 11.04.2018
	Referenz: G48, 16.10.2019
	Name: 836xxx_TDS_EN
	Seite 2 von 2