

## EUROLUB KÜHLERSCHUTZ DD-40

KÜHLERSCHUTZ DD-40 is a radiator protection based on ethylene glycol and glycerin. It contains an inhibitor package based on silicate and salts of organic acids (Si-OAT coolant). It is nitrite, amine, phosphate and borate free. KÜHLERSCHUTZ DD-40 must be diluted with water before use.

<b>Produkteigenschaften: Anwendung:</b>	KÜHLERSCHUTZ DD-40 protects all modern engines, especially heavy-duty aluminum engines, excellent against frost, rust and overheating. It prevents corrosion and deposition in the cooling system with the important components. Since the special application advantages of the KÜHLERSCHUTZ DD-40, such as good aluminum protection and longer intervals, Are only achieved when the KÜHLERSCHUTZ DD-40 is used alone, mixing with other radiator protection agents is not recommended.		
<b>Can be used for:</b>	VW TL 774 Ausf. J (approved for all vehicle brands of the VW Group)  ASTM D 3306 CUNA NC 956-16 BS 6580: 2010		
	Audi G 013 A8J M1 Dacia 77 11 428 133 Renault 77 11 428 133 Seat G 013 A8J M1 Skoda G 013 A8J M1 VW G 013 A8J M1		
<b>Delivery:</b>	Art.-Nr. 838015 Art.-Nr. 838020 Art.-Nr. 838060 Art.-Nr. 838208 Art.-Nr. 838100	12 x 1,5 Liter 20 Liter 60 Liter 208 Liter 1.000 Liter	plastic bottle plastic can hobbock drum IBC

# PRODUCT INFORMATION



## Water mixtures:

(Do not mix below -20 ° C, since less than 33% Antifreeze no corrosion protection is guaranteed.)

Ratio antifreeze	Ratio water	Frost protection to:
1 part	2 parts	-20°C
1 part	1,5 parts	-27°C
1 part	1 part	-37°C

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.