

EUROLUB KÜHLERSCHUTZ FGMR Ultra

Description/Applications:	<p>KÜHLERSCHUTZ FGMR Ultra gives outstanding protection against frost, corrosion and overheating in all modern engines, but especially highly loaded aluminium engines. It effectively protects against corrosion and deposits in the cooling system with its vital parts, the coolant channels in the block and cylinder head, the radiator, the water pump and the heatercore.</p> <p>KÜHLERSCHUTZ FGMR Ultra must be diluted with water before use. It is hard water compatible and can be mixed with tap water(*) before filling into the cooling system to give solutions in the concentration range of 30 to 50 % by volume.</p> <p>(*)= For preparation of the coolant use clean, not overly hard water. Waste water from mining, sea water, brackish water, brine, industrial waste water are all unsuitable.</p>
----------------------------------	---

Can be used with:	<p>Ford WSS-M97B44D GM 6277M Renault Typ D</p>
--------------------------	--

Delivery:	<table> <tr> <td>Art.-Nr. 839015</td> <td>12 x 1 Liter</td> <td>bottle</td> </tr> <tr> <td>Art.-Nr. 839005</td> <td>4 x 5 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 839020</td> <td>20 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 839060</td> <td>60 Liter</td> <td>hobbock</td> </tr> <tr> <td>Art.-Nr. 839208</td> <td>208 Liter</td> <td>drum</td> </tr> <tr> <td>Art.-Nr. 839100</td> <td>Container</td> <td>IBC</td> </tr> </table>	Art.-Nr. 839015	12 x 1 Liter	bottle	Art.-Nr. 839005	4 x 5 Liter	can	Art.-Nr. 839020	20 Liter	can	Art.-Nr. 839060	60 Liter	hobbock	Art.-Nr. 839208	208 Liter	drum	Art.-Nr. 839100	Container	IBC
Art.-Nr. 839015	12 x 1 Liter	bottle																	
Art.-Nr. 839005	4 x 5 Liter	can																	
Art.-Nr. 839020	20 Liter	can																	
Art.-Nr. 839060	60 Liter	hobbock																	
Art.-Nr. 839208	208 Liter	drum																	
Art.-Nr. 839100	Container	IBC																	

Water mixtures:		
(Do not mix below -20 ° C, since less than 33% Antifreeze no corrosion protection is guaranteed.)		
Ratio antifreeze	Ratio water	Frost protection to:
1 part	2 parts	-20°C
1 part	1,5 parts	-27°C
1 part	1 part	-37°C

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 24.08.2020, made 14.11.2017
	Referenz:
	Name: 839xxx_TDS_EN
	Seite 1 von 1