Revision 24.06.2021 (GB) Version 1.1

### **EUROFUEL 4-TAKT GERÄTEBENZIN**

880xxx



### ! SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Name of product EUROFUEL 4-TAKT GERÄTEBENZIN

Art-Nr 880xxx

UFI: GJE2-K05D-J000-X9X5

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### **Identified** uses

**Product categories [PC]** 

PC13 - Fuels

### 1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor EUROLUB GmbH

Freisingerstraße 25-27, D-85386 Eching b. München Phone +49 8165 9591-0, Fax +49 8165 9591-210

E-Mail info@eurolub.com Internet www.eurolub.com

### 1.4. Emergency telephone number

**Emergency advice** 

Phone +49 8165 9591-0

This number is only available at office times.

### **SECTION 2: Hazards identification**

Hazard classes and Hazard

## 2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

categories		
Flam. Liq. 1	H224	
Skin Irrit. 2	H315	
STOT SE 3	Н336	
Asp. Tox. 1	H304	

### Hazard statements for physical hazards

H224 Extremely flammable liquid and vapour.

### Hazard statements for health hazards

H304 May be fatal if swallowed and enters airways.

H411

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.
Hazard statements for environmental hazards

H411 Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

**Aquatic Chronic 2** 

EUROLUB GmbH Page 1/9

Hazard Statements Classification procedure

**No. 1907/2006 (REACH)**Revision 24.06.2021 (GB) Version 1.1

### **EUROFUEL 4-TAKT GERÄTEBENZIN**

880xxx



### Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]









GHS02

)2 GHS07

GHS08

GHS09

### Signal word

Danger

### Hazard statements for physical hazards

H224 Extremely flammable liquid and vapour.

### Hazard statements for health hazards

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

### Hazard statements for environmental hazards

H411 Toxic to aquatic life with long lasting effects.

### **Precautionary Statements**

General

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use extinguishing powder or sand for extinction.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal

P501 Dispose of contents / container in accordance with local regulations.

### Hazardous ingredients for labelling

isopentane, Naphtha (petroleum), full-range alkylate

### 2.3. Other hazards

### Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

not applicable

### 3.2. Mixtures

### **Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
64741-64-6	265-066-7	Naphtha (petroleum), full-range alkylate	50 - 100	Carc. 1B, H350 / Muta. 1B, H340 / Asp. Tox. 1, H304
78-78-4	201-142-8	isopentane	10 - 20	Flam. Liq. 1, H224 / Asp. Tox. 1, H304 / STOT SE 3, H336 / Aquatic Chronic 2, H411

EUROLUB GmbH Page 2/9

Revision 24.06.2021 (GB) Version 1.1

### **EUROFUEL 4-TAKT GERÄTEBENZIN**

880xxx



### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### **General information**

In the event of persistent symptoms receive medical treatment.

Take affected person into fresh air.

Do not leave casualty unattended.

Take away from danger area and lay down affected person.

### In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In case of inhalation remove the casualty into fresh air and seek medical advice.

### In case of skin contact

In case of contact with skin wash off with soap and water.

Remove contaminated clothing immediately, even underwear and shoes.

### In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

### In case of ingestion

Do not induce vomiting.

If swallowed by mistake drink plenty of water and seek medical treatment.

Rinse out mouth thoroughly with water.

### 4.2. Most important symptoms and effects, both acute and delayed

Physician's information / possible symptoms

Eye defects

vomiting

Headache

Nausea

Dizziness

## 4.3. Indication of any immediate medical attention and special treatment needed Treatment (Advice to doctor)

no

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

Water spray jet

### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

In fires, hazardous combustion gases are formed:

Carbon monoxide (CO)

Carbon dioxide (CO2)

### 5.3. Advice for firefighters

### Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Wear full protective clothing.

EUROLUB GmbH Page 3/9

Revision 24.06.2021 (GB) Version 1.1

### **EUROFUEL 4-TAKT GERÄTEBENZIN**

880xxx



### **Additional information**

Collect contaminated firefighting water separately, must not be discharged into the drains.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### For non-emergency personnel

Ensure adequate ventilation.

Remove persons to safety.

### 6.2. Environmental precautions

Collect contaminated water / firefighting water separately.

Do not discharge into the drains/surface waters/groundwater.

### 6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

### **Additional Information**

Informations for personal protective equipment see chapter 8.

### 6.4. Reference to other sections

No information available.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

### Advice on safe handling

In case of free handling thoroughly sucking off vapours is necessary.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Use explosion-protected equipment / fittings.

### General protective measures

Do not inhale vapours.

Do not inhale gases/vapours/aerosols.

### Hygiene measures

Cloths contaminated with product should not be kept in trouser pockets.

At work do not eat, drink and smoke.

Work in rooms with good ventilation.

Keep away from food and drink.

### Advice on protection against fire and explosion

The product is combustible.

Vapours can form an explosive mixture with air.

### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Store in heated containers.

### Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from heat and direct solar radiation.

Protect from heat/overheating.

Storage group

3

Fire class B

EUROLUB GmbH Page 4/9

Revision 24.06.2021 (GB) Version 1.1

**EUROFUEL 4-TAKT GERÄTEBENZIN** 

880xxx



### 7.3. Specific end use(s)

No information available.

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2004/37/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
78-78-4	isopentane	8 hours	3000	1000	

### 8.2. Exposure controls

### **Respiratory protection**

In case of insufficient ventilation or long-term effect use breathing apparatus.

### Hand protection

Gloves (solvent-resistant)

### Eye protection

safety goggles with side protection

### Other protection measures

Solvent-resistant protective clothing

### Appropriate engineering controls

No data available

### **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

AppearanceColourOdourliquidcolourless, clearlike paraffine

Odour threshold not determined

### Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling range	25 - 200 °C		1013 hPa		
Melting point / Freezing point	not determined				
Flash point	< 0 °C			DIN 51755	
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	> 400 °C				
Self ignition temperature	not determined				
Lower explosion limit	1,3 Vol-%				

EUROLUB GmbH Page 5/9

No. 1907/2006 (REACH)

Revision 24.06.2021 (GB) Version 1.1

### **EUROFUEL 4-TAKT GERÄTEBENZIN**

880xxx



	Value	Temperature	at	Method	Remark
Upper explosion limit	7,6 Vol-%				
Vapour pressure	not determined				
Relative density	0,72 g/cm3				
Vapour density	not determined				
Solubility in water	not determined				
Solubility/other	not determined				
Partition coefficient noctanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity kinematic	< 1	20 °C			
Solvent content	100 %				
Oxidising properties No information available.					
<b>Explosive properties</b> No information available.					
<b>9.2. Other information</b> flammable liqiud					

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

No information available.

### 10.3. Possibility of hazardous reactions

Formation of explosive gas/air mixtures.

### 10.4. Conditions to avoid

Thermal decomposition can lead to the escape of irritating gases and vapours.

## 10.5. Incompatible materials Substances to avoid

Alkali (lye), concentrated Acid, concentrated Oxidising agent, strong

### 10.6. Hazardous decomposition products

No information available.

EUROLUB GmbH Page 6/9

No. 1907/2006 (REACH)

Revision 24.06.2021 (GB) Version 1.1

**EUROFUEL 4-TAKT GERÄTEBENZIN** 

880xxx



term trials.

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

### Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark	
LD50 acute oral	> 3000 mg/kg	rat			
LD50 acute dermal	> 2000 mg/kg	rat			
Skin irritation		No information available.			
Eye irritation		No information available.			
Skin sensitization		No information available.			
Sensitization respiratory system		No information available.			

### **Subacute Toxicity - Carcinogenicity**

	Value	Species	Method	Validation
Mutagenicity	No data available			
Reproduction- Toxicity				Indications of toxic effects are available from reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-

### Specific target organ toxicity (single exposure)

No information available.

respiratory system

### Specific target organ toxicity (repeated exposure)

NOEC 1 - 10 mg/l

No information available.

### **Aspiration hazard**

May be fatal if swallowed and enters airways.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

### **Ecotoxicological effects**

	Value	Species	Method	Validation
Tiob.	NOEC 1 - 10 mg/l			

NOEC 1 - 10 mg/l Fish

Daphnia

NOEC 10 - 100 mg/l Algae

### 12.2. Persistence and degradability

**EUROLUB GmbH** Page 7/9

No. 1907/2006 (REACH)

Revision 24.06.2021 (GB) Version 1.1

### **EUROFUEL 4-TAKT GERÄTEBENZIN**

880xxx



Elimination rate Method of analysis Method Validation

Biological readily degradable degradability

### 12.3. Bioaccumulative potential

Because of the n-octanol/water distribution coefficient (log K o/w) accumulation in organisms is possible.

### 12.4. Mobility in soil

not determined

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Other adverse effects

No information available.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste code No.

Name of waste

13 07 03\*

other fuels (including mixtures)

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

### **Recommendations for the product**

Remove in accordance with local official regulations.

### **General information**

nc

### **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1203	1203	1203
14.2. UN proper shipping nan	n <b>e</b> GASOLINE	PETROL	Gasoline
14.3. Transport hazard class(e	esB	3	3
14.4. Packing group	II	II	II
14.5. Environmental hazards	Yes	Yes	Yes

### 14.6. Special precautions for user

no

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available.

### Land and inland navigation transport ADR/RID

Hazard label(s) 3

Tunnel restriction code D/E

Classification code F1

### **Marine transport IMDG**

MARINE POLLUTANT

EUROLUB GmbH Page 8/9

Revision 24.06.2021 (GB) Version 1.1

**EUROFUEL 4-TAKT GERÄTEBENZIN** 

880xxx



### **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Other regulations (EU)

Regulation (EC) No 648/2004 (Detergents regulation).

**VOC** standard

**VOC content** 100 % **VOC value** 720 g/L

**National regulations** 

**Restriction of occupation**No information available.

Water hazard class 2 self-classification

### 15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

### **SECTION 16: Other information**

### Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

### **Further information**

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 1.0

H224	Extremely flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H350	May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H411	Toxic to aquatic life with long lasting effects.

EUROLUB GmbH Page 9/9